


Recommended P.C.B Layout(Top View)
(PCB Board Tolerance±0.05)



SIM Card Pin Assignment	
Pin#	Name
C1	VCC
C2	RST
C3	CLK
C5	GND
C6	VPP
C7	I/O
SW	Switch

SPECIFICATION

- 1.Material&Finish**
Housing:LCP(UL94V-0),Black
Contact:Copper Alloy,Gold Flash On Contact Area,
Gold Flash On Solder Tails,Over Nickel
Shell:Stainless Steel
Gold Flash On Solder Tails,Over Nickel
- 2.Electrical Characteristics**
Current Rating:0.5A
Voltage Rating:50V
Dielectric Withstanding Voltage:100V AC
Insulation Resistance:100 Megaohms Min. 100V DC
Contact Resistance:100 Milliohms Max.
- 3.Mechanical Characteristics**
Durability:3000 Cycles
- 4.RoHS Compliant**

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY	
22372		MEI	
		CHECKED BY	
		HZF	
		DRAWING BY	
		LZX	
SCALE	NONE	REV.	A0

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
X. ±0.25
.X ±0.20
.XX ±0.10
ANG. ±3°

UNIT	mm	NO.	REV.	A0	NEW RELEASE	CHK	HZF	01/28/2022
					REVISIONS		DATE	