



△ SPECIFICATION
 Current Rating:1 Amps
 Withstanding Voltage:500V(One Minute)
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 At DC 500V
 Operating Temperature:-40°C~+85°C
 Insulator:PBT+30%G.F.(UL94V-0),Blue
 Contact:Brass,Gold Flash On Contact Area
 Tin Plated On Solder Tails,Over Nickel
 Shell:SPCC,Nickel Plated Front,Tin Plated Rear
 Screw:12L14,Nickel Plated
 Nut:C3602,Nickel Plated
 RoHS Compliant

△ Pin	A	B	C	D
9	16.33	24.99	30.81	19.20
15	24.80	33.32	39.20	27.70
25	38.38	47.04	53.04	41.10
37	54.84	63.50	69.40	57.30
50	52.20	61.00	67.00	55.10

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. △		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 △.X* ±3* .XX ±0.25 .XX* ±1* .XXX ±0.05 .XXX* ±0.5*
22391		MEI		
		CHECKED BY HZF		
SCALE NONE		DRAWING BY CYP		UNIT mm
REV. A2		REV. A2		△ A2 Modify data HZF 08/11/2017
				△ A1 Modify data HZF 04/20/2017
				△ A0 NEW RELEASE HZF 10/21/2009
				NO.REV. REVISIONS CHK DATE