



Recommended P.C.B. Layout(Top View)

SPECIFICATION
 Current Rating:1.5A
 Voltage Rating:125V AC
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:500 Megaohms Min.
 At 500V DC
 Withstanding Voltage:1000V AC RMS
 50Hz Or 60Hz,1 Minute
 Operation Temperature:-40°C~+85°C
 Housing:PBT+G.F.(UL94V-0),Black
 Contact:Phosphor Bronze,ø0.46mm
 Gold Flash Over All,Over Nickel
 Shield:Brass,Nickel Plated
 The Marts Modular Plug Conformaing
 To FCC Part 68
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.20 X.* ±2° .XX ±0.15 X.* ±1° .XXX ±0.10
22800		MEI		
		CHECKED BY		
		HZF		
		DRAWING BY		
		LSM		
SCALE	NONE	REV.	A0	UNIT
				mm

NO.	REV.	DESCRIPTION	CHK	DATE
△	A0	NEW RELEASE	HZF	06/26/2024
		REVISIONS		