




Recommended P.C.B. Layout (Top View)  
(PCB Board Tolerance  $\pm 0.05$ )



**SPECIFICATION**

Current Rating:3A  
 $\Delta$ Withstand Voltage:1000V AC Min./Minute  
 Contact Resistance:20 Milliohms Max.  
 Insulation Resistance:1000 Megaohms Min.  
 Operation Temperature:-40°C~+105°C  
 Housing:PA6T(UL94V-0),Black  
 Contact:Phosphor Bronze,Gold Flash Over Nickel  
 RoHS Compliant

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. $\pm 0.25$ X.* $\pm 2^{\circ}$ .X $\pm 0.20$ .X* $\pm 1.5^{\circ}$ .XX $\pm 0.15$ .XX* $\pm 1^{\circ}$ .XXX $\pm 0.10$ .XXX* $\pm 0.5^{\circ}$				
00691		EMILY						
		CHECKED BY						
		HZF						
		DRAWING BY						
		SAN						
SCALE	NONE	REV.	A1	UNIT	mm			

NO.	REV.	REVISIONS	CHK	DATE
	A1	Modify Data	HZF	07/26/2021
	A0	NEW RELEASE	HZF	11/19/2013