






 Current Rating:7A AC/DC
 Voltage Rating:250V AC Max.
 Operating Temperature:-25°C~+85°C
 Insulation Resistance:1000 Megaohms Min.
 Contact Resistance:10 Milliohms Max.
 Insulator:PA66(UL94V-0)
 Terminal:Brass,Tin Plated Over Nickel
 RoHS Compliant



Pin	A	B
02	3.96	7.92
03	7.92	11.92
04	11.88	15.84
05	15.84	19.84
06	19.80	23.80
07	23.76	27.88
08	27.72	31.74
09	31.68	35.86
10	35.64	39.90
11	39.60	43.84
12	43.56	47.92
13	47.52	51.92
14	51.48	55.92

4U CON 元化興業股份有限公司
4U CON TECHNOLOGY INC.

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE
 .X ± 0.5
 .XX ± 0.35
 ANG.

UNIT	
mm	

B3

UNIT	
mm	

	B3	Modify Data	HZF	03/13/2015
	B2	Modify Data	HZF	01/03/2013
	B1	Modify Data	HZF	09/15/2009
	B0	NEW RELEASE	BECKY	11/14/2005
NO. REV.	REVISIONS		CHK	DATE