

SPECIFICATION

1.General Characteristics

3.0mm Micro-Fit Receptacle Housing 2XXX
Black Insulator

2.Material&Finish

Housing:PA66(UL94V-0),Black




3.Electrical Characteristics

Current Rating:3A AC/DC
Voltage Rating:250V AC/DC
Insulation Resistance:1000 Megaohms Min.
Withstand Voltage:1500V AC/Minute



4.Environmental Characteristics

Temperature Range:-25°C~+85°C

5.RoHS Compliant



02~04 Pin



06~24 Pin



Pin	A	B
02	--	3.85
04	3.0	6.85
06	6.0	9.85
08	9.0	12.85
10	12.0	15.85
12	15.0	18.85
14	18.0	21.85
16	21.0	24.95
18	24.0	27.95
20	27.0	30.95
22	30.0	33.95
24	33.0	36.95

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

02597

SCALE NONE

APPROVED BY

EMILY

CHECKED BY

HZF


DRAWING BY

SONG

REV.

A3

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE
X. ±0.5
X ±0.25
.XX ±0.2
.XXX ±0.08

UNIT
mm

A3

Modify Data

HZF

09/16/2014

A2

Modify Data

HZF

05/20/2013

A1

Modify Data

HZF

11/30/2009

A0

NEW RELEASE

NO. REV.

REVISIONS

CHK

DATE