



△ SPECIFICATION
 △ Current Rating: 1 Amps
 Withstanding Voltage: 500V For 1 Minute
 Contact Resistance: 30 Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min.
 At 500V DC
 Operating Temperature: -40°C ~ +85°C
 △ Insulator: PBT+30%G.F.(UL94V-0), Black
 Contact: Brass, Gold Flash On Contact Area,
 Tin Plated On Solder Tails, Over Nickel
 Shell: SPCC, Nickel Plated
 Boardlock: SPCC, Tin Plated
 Screw: 12L14, Nickel Plated
 RoHS Compliant

Pin	A	B	C	D	E
15	16.33	24.99	30.81	2.29	0.25
26	24.80	33.32	39.20	2.29	0.50
44	38.38	47.04	53.04	2.29	0.50
62	54.84	63.50	69.40	2.41	0.60

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. △		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 .X* ±3* .XX ±0.25 .XX* ±1* .XXX ±0.05 .XXX* ±0.5*	△ B4	Modify Data	HZF	03/30/2019
02614		MEI			△ B3	Modify Data	HZF	05/08/2018
		CHECKED BY			△ B2	Modify Data	HZF	12/24/2015
SCALE NONE		DRAWING BY		△ B1	Modify Data	HZF	09/19/2014	
		CYP		△ B0	NEW RELEASE	HZF	04/10/2013	
REV.	B4	UNIT	mm	NO. REV.	REVISIONS		CHK	DATE