







SPECIFICATION

Current Rating:1 Amps
Withstanding Voltage:500V(One Minute)
Insulation Resistance:1000 Megaohms Min. At DC 500V
Contact Resistance:30 Milliohms Max.
Operating Temperature: -40°C~+85°C
Contact:Brass

Gold Plated On Contact Area,
Tin Plated On Solder Tails,Over Nickel

Insulator:PBT+30%G.F.(UL94V-0),Black
Shell:SPCC,Nickel Plated Front,Tin Plated Rear
RoHS Compliant



Pin	A	B	C	D
09	16.92	24.99	30.81	19.20
15	25.25	33.32	39.20	27.70
25	38.96	47.04	53.04	41.10
37	55.42	63.50	69.40	57.30
50	52.81	61.00	67.00	55.10

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

03263

SCALE NONE

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

CYP

REV.

A0

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE

.X ±0.38 .X* ±3*
.XX ±0.25 .XX* ±1*
.XXX ±0.05 .XXX* ±0.5*

UNIT
mm



NO. REV.

NEW RELEASE
REVISIONS

CHK HZF
DATE 12/07/2016