



**SPECIFICATION**  
 Current Rating:1A AC/DC  
 Voltage Rating:250V AC/DC  
 Withstanding Voltage:500V AC/Minute  
 Contact Resistance:20 Milliohms Max.  
 Insulation Resistance:1000 Megaohms Min.  
 Temperature Range:-40°C~+105°C  
 Housing:PBT+G.F.(UL94V-0)  
 Contact:Brass,Selective Gold Plated Over Nickel  
 RoHS Compliant

Pin	A	B
08	6.0	13.2
10	8.0	15.2
12	10.0	17.2
14	12.0	19.2
16	14.0	21.2
18	16.0	23.2
20	18.0	25.2
22	20.0	27.2
24	22.0	29.2
26	24.0	31.2
28	26.0	33.2
30	28.0	35.2
34	32.0	39.2
36	34.0	41.2
40	38.0	45.2
44	42.0	49.2
50	48.0	55.2
56	54.0	61.2

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No. 03446

APPROVED BY EMILY  
 CHECKED BY HZF  
 DRAWING BY SONG

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE  
 X. ±0.30 X.\* ±3.0\*  
 .X ±0.20 .X\* ±2.0\*  
 .XX ±0.15 .XX\* ±1.0\*  
 .XXX ±0.10 .XXX\* ±0.5\*

UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
AO		NEW RELEASE	HZF	06/05/2012

SCALE NONE

REV. AO

NO. REV. REVISIONS CHK DATE