



△△ SPECIFICATION
 Current Rating:1.5A Max.
 Voltage Rating:150V AC Max.
 Operating Temperature:-40°C~+85°C
 Insulation Resistance:500 Megaohms Min. (Initial)
 At 500V DC For 1 Minute
 Contact Resistance:20 Milliohms Max.(Initial)
 Dielectric Withstanding Voltage:
 1000V RMS. At 60Hz,1 Minute Between
 Adjacent Contacts
 1500V RMS. At 60Hz,1 Minute Between
 Shield And Contacts
 Housing:PBT+G.F.(UL94V-0),Gray
 Contacts:Phosphor Bronze
 Gold Plated 6u" Over All,Over Nickel
 Cavity Confirms To FCC Rules And Regulations
 Part 68,Subpart F.
 RoHS Compliant

Item:Port Of Position

△△ Ports	A	B	C
02	23.9	23.6	11.65
03	35.55	35.25	23.3
04	47.20	46.9	34.95
05	58.85	58.55	46.6
06	70.5	70.2	58.25
07	82.15	81.85	69.9
08	93.8	93.5	81.55
09	105.45	105.15	93.2
10	117.1	116.8	104.85
11	128.75	128.45	116.5
12	140.4	140.1	128.15

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. △△
04928

APPROVED BY MEI
 CHECKED BY HZF
 DRAWING BY SONG
 REV. A2

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 △ .X ±0.25
 .XX ±0.13
 .XXX ±0.05

NO.	REV.	REVISIONS	CHK	DATE
△△	A2	Modify Data	HZF	11/26/2020
△	A1	Modify Data	HZF	07/08/2014
△	A0	NEW RELEASE	HZF	07/10/2008

SCALE NONE REV. A2 UNIT mm