



**△ SPECIFICATION**

Signal Contact Current Rating:5.0 Amp  
 Power Contact Current Rating:10~40 Amp  
 Contact Resistance:10 Milliohms Max.  
 Insulation Resistance:5000 Megaohms Min.  
 Dielectric Withstand Voltage:1000V AC For 1 Minute  
 Operation Temperature:-55°C~+125°C  
 Coaxial Contact Impedance:75 Ohms  
 Shell:Steel,Tin Plated  
 Insulator:PBT+30%G.F.(UL94V-0),Black  
 Coaxial Center Insulator:Teflon,White  
 Signal Contact:Brass,Gold Flash Over Nickel  
 Power Contact:Brass,Gold Flash Over Nickel  
 Coaxial Contact:Brass,Gold Flash Over Nickel  
 RoHS Compliant



**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE  .XX ±0.3 ANG. ±2°
07539		EMILY		
		CHECKED BY		
DRAWING BY		HZF		
SCALE		REV.		UNIT
NONE		B1		mm

NO.	REV.	REVISIONS	CHK	DATE
△ B1		Modify Data	HZF	07/31/2012
△ B0		NEW RELEASE	BECKY	02/08/2006