



△△ SPECIFICATION
 Current Rating:16 Amp/Way Max.
 Voltage Rating:300V AC
 Contact Resistance:20 Milliohms Max.
 Withstanding Voltage:2500V AC(1 Minute)
 Test Time=60 Sec./1 PCS
 Operation Temperature:-40°C~+105°C
 Soldering Reliability:Test Temperature=250°C±10°C/
 5 Seconds Max.
 Wire Range:12~26 AWG
 Torque:5.0 Kgf.cm/M3
 Insulator Body(Housing):Polyamide(UL94V-0),Green
 Contact(Metal Housing):Copper Alloy,Nickel Plated
 Wire Guard:Copper Alloy,Tin Plated
 Screw:Steel,Galvanized With Cr3+ Plated
 RoHS Compliant

4U CON 元化興業股份有限公司
 4U CON TECHNOLOGY INC.

DRAWING No. △△		APPROVED BY MEI		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.50 .X ±0.30 .XX ±0.20 ANG. ±1°	△ A4	Modify Data	HZF	08/07/2014
09172		CHECKED BY HZF			△ A3	Modify Data	HZF	02/12/2014
		DRAWING BY YBL			△ A2	Modify Data	HZF	12/16/2011
SCALE	NONE	REV.	A4	△ A1	Modify Data	HZF	06/29/2010	
				△ A0	NEW RELEASE	HZF	04/10/2009	
				NO.REV.	REVISIONS	CHK	DATE	

