

△△ SPECIFICATION

- Current Rating:16 Amp/Way Max.
- Voltage Rating:300V AC
- Contact Resistance:20 Milliohms Max.
- Withstanding Voltage:2500V AC(1 Minute)
Test Time=60 Sec./1 PCS
- Operation Temperature:-40°C~+105°C
- Soldering Reliability:Test Temperature=250°C±10°C/
5 Seconds Max.
- Wire Range:12~26 AWG
- Torque:5.0 Kgf.cm/M3
- Insulator Body(Housing):Polyamide(UL94V-0),Green
- △ Contact(Metal Housing):Copper Alloy,Nickel Plated
- Wire Guard:Copper Alloy,Tin Plated
- Screw:Steel,Galvanized With Cr3+ Plated
- RoHS Compliant

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. △△

09177

APPROVED BY

MEI

CHECKED BY


HZF

DRAWING BY

YBL

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
X. ±0.50
.X ±0.30
.XX ±0.20
ANG. ±1°

UNIT
mm



△	A4	Modify Data	HZF	08/07/2014
△	A3	Modify Data	HZF	02/12/2014
△	A2	Modify Data	HZF	12/16/2011
△	A1	Modify Data	HZF	06/29/2010
△	A0	NEW RELEASE	HZF	04/10/2009
NO. REV.	REVISIONS		CHK	DATE