


File No.	271IG13217	SHEET	1/1









⚠1 SPECIFICATION


Current Range:
Non−Switching:100mA 50V DC
Switching:25mA 24V DC
Withstanding Voltage:500V AC 50Hz Or 60Hz For 1 Minute
Contact Resistance:50 Milliohms Max.(Initial)
Insulation Resistance:100 Megaohms Min. At 500V DC,60s±5s
⚠2 Operation Temperature Range:−40°C~+85°C
Storage Temperature Range:−40°C~+85°C
Operation Force:9.8N Max.
RoHS Compliant

Pin	A	B
02	6.44	2.54
03	8.98	5.08
04	11.52	7.62
05	14.06	10.16
06	16.60	12.70
07	19.14	15.24
08	21.68	17.78
09	24.22	20.32
10	26.76	22.86
12	31.84	27.94





Schematic(Typ.)



(2,3,4,5,6,7,8,9,10,12 Pos Avail)

⚠3 ⚠2 ⚠1 Item	Description	Q'ty	Material	Remark
①	Terminal	1	Brass	Gold Plated Over Nickel
②	Cover	1	PBT,UL94V−0	Red
③	Stem	2~12	PBT,UL94V−0	White
④	Contact	2~12	C7035	Gold Plated Over Nickel
⑤	Base	1	PA66+20%G.F.	Black

4UCON 元化興業股份有限公司 4UCON TECHNOLOGY INC.

DRAWING No. ⚠0 ⚠1	APPROVED BY MEI	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
09805	CHECKED BY HZF	10mm Over ±0.20
	DRAWING BY CYP	10mm Below ±0.10
SCALE NONE	REV. B3	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
⚠3	B3	Modify Data	HZF	07/13/2018
⚠2	B2	Modify Data	HZF	08/11/2015
⚠1	B1	Modify Data	HZF	04/04/2014
⚠0	B0	Modify Data	HZF	03/14/2009
⚠0	B0	NEW RELEASE	HZF	03/14/2009