



△△ SPECIFICATION
 Dielectric Withstanding Voltage:1000V AC Per Minute
 Contact Resistance:10 Milliohms Max.
 Insulation Resistance:5000 Megaohms Min.
 Operation Temperature:-55°C~+125°C
 Insulator:PBT+30%G.F.(UL94V-0),White
 △ Contact:Brass,Gold Flash Over Nickel
 Metal Shell:Steel,Tin Plated Over Nickel
 RoHS Compliant

Pin	A±0.25	B±0.13	C±0.38	D±0.25	E±0.25
09	16.33	24.99	30.81	19.28	11.08
15	24.66	33.32	39.14	27.51	19.39
25	38.38	47.04	53.04	41.28	33.24
37	54.84	63.50	69.32	57.71	49.86

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. 10585

APPROVED BY EMILY
 CHECKED BY HZF
 DRAWING BY SAN

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 .X ±0.3
 .XX ±0.3
 .XXX ±0.3
 ANG. ±2°

SCALE NONE REV. A4 UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△	A4	Modify Spec.	HZF	05/29/2014
△	A3	Modify P/N Code	HZF	01/21/2011
△	A2	Modify Data	HZF	12/18/2009
△	A1	Modify Dim.:7.9-->7.2&Add Spec.	BECKY	2004/11/04
△	A0	NEW RELEASE		