



**SPECIFICATION**  
 Current Rating:1.5 Ampere Per Contact  
 Contact Resistance:30 Milliohms Max.  
 Insulation Resistance:1000 Megaohms Min.  
 Dielectric Withstanding Voltage:500V AC  
 Operation Temperature:-40°C~+85°C  
 Housing:LCP(UL94V-0),Black  
 △ Contact:Phosphor Bronze  
     Gold Plated 15u" On Contact Area,Tin  
     Plated On Solder Tails,Over Nickel  
 RoHS Compliant

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

|             |      |             |    |  |
|-------------|------|-------------|----|--|
| DRAWING No. |      | APPROVED BY |    | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE<br>.X ±0.30<br>.XX ±0.25<br>ANG. ±3° |
| 11074       |      | EMILY       |    |  |
|             |      | CHECKED BY  |    |  |
|             |      | HZF         |    |  |
|             |      | DRAWING BY  |    |  |
|             |      | CYP         |    |  |
| SCALE       | NONE | REV.        | A2 | UNIT   |
|             |      |             |    | mm   |

|     |      |             |     |            |
|-----|------|-------------|-----|------------|
| NO. | REV. | REVISIONS   | CHK | DATE       |
| △A2 |      | Modify Data | HZF | 07/30/2015 |
| △A1 |      | Modify Data | HZF | 11/09/2011 |
| △A0 |      | NEW RELEASE | HZF | 04/27/2011 |