



Recommended P.C.B. Layout(Bottom View)

SPECIFICATION

Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min. At 500V DC
 Rated Voltage And Current:1.5A At 250V AC Min.
 Withstand Voltage:500V AC(RMS) For 1 Minute(Rev. 2.0)
 Durability(Life Test):1500 Cycles
 Insertion Force:35N Max.
 Extraction Force:10N Min.
 Contact Finish:Gold Plated 30u" On Contact Area,Tin
 Plated On Solder Tails,Over Nickel
 RoHS Compliant

No.	Name	Material	Remark	Q'ty
①	Housing	PBT+G.F.	Black	1
②	Contact	Phosphor Bronze		4
③	Shell	Brass	Nickel Plated	1

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.38 .X ±0.25 .XX ±0.13 .XXX ±0.05
11084		EMILY		
		CHECKED BY		
		HZF		
		DRAWING BY		
		HAO		
SCALE	NONE	REV.	A0	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△ A0		NEW RELEASE	HZF	03/24/2015