



△ SPECIFICATION

Current:1A
 Dielectric Strength:1000V AC Minute
 Contact Resistance:20 Milliohms Max.
 Insulation Resistance:5000 Megaohms Min.
 Operation Temperature:-55°C~+105°C
 Housing:PA6T(UL94V-0),Black
 △△ Contact:Brass,Gold Flash Over Nickel
 No. Of Contacts:04~100 Contacts
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

| | | | | |
|-------------|------|----------------|----|--|
| DRAWING No. | | APPROVED BY | | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.38 .XX ±0.25 ANG. ±5° |
| 13498 | | EMILY | | |
| | | CHECKED BY HZF | | |
| | | DRAWING BY HAO | | UNIT mm |
| SCALE | NONE | REV. | A4 | |

| | | | |
|----------|--------------|-------|------------|
| △ A4 | Modify Spec. | HZF | 05/23/2015 |
| △ A3 | Modify Data | HZF | 04/15/2013 |
| △ A2 | Modify Data | HZF | 11/28/2012 |
| △ A1 | Modify Data | HZF | 08/02/2010 |
| △ A0 | NEW RELEASE | BECKY | 08/08/2005 |
| NO. REV. | REVISIONS | CHK | DATE |