



SPECIFICATION

- Material&Finish**
Insulator:LCP(UL94V-0),Black
Contact:Brass,Tin Plated
Solder Tabs:Brass,Tin Plated Over Nickel
- Electrical Characteristics**
Current Rating:5A AC,DC
Voltage Rating:250V AC,DC
Contact Resistance:20 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
△ Withstand Voltage:1500V AC/Minute
- Environmental Characteristics**
Temperature Range:-40°C~+105°C
- RoHS Compliant**

Pin	A	B	C
2	--	6.65	4.30
4	3.00	9.65	7.30
6	6.00	12.65	10.30
8	9.00	15.65	13.30
10	12.00	18.65	16.30
12	15.00	21.65	19.30
14	18.00	24.65	22.30
16	21.00	27.65	25.30
18	24.00	30.65	28.30
20	27.00	33.65	31.30
22	30.00	36.65	34.30
24	33.00	39.65	37.30

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. △ 18078

APPROVED BY Jason Wu
CHECKED BY Leo Han
DRAWING BY Michelle Lee

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
.X ±0.30
.X ±0.25
.XX ±0.20
.XXX ±0.05
ANG. ±1°

SCALE NONE REV. B1 UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△	B1	Modify Data	HZF	07/21/2025
△	B0	Modify Data	HZF	02/20/2023
△	B0	NEW RELEASE	HZF	02/20/2023