



Recommended P.C.B. Layout(T=1.6mm)
Tolerance:±0.05(Printed-Top View)

SPECIFICATION

Rating:AC 100V 2A Or DC 24V 1A Max.
Withstanding Voltage:250V AC R.M.S.
(50 To 60Hz)For 1 Minute
Contact Resistance:Pin-Contact:30 Milliohms Max.
Plug Cover-Socket:50 Milliohms Max.
Insulation Resistance:50 Megaohms Min.
At 250V DC
Operation Temperature Range:-40°C~+85°C
RoHS Compliant

No.	Description	Q'ty	Material	Remark
①	Housing	1	PBT(UL94V-0)	Black
②	Cover	1	PBT(UL94V-0)	Black
③	Contact Foot	6	Brass	Silver Plated
④	Contact Foot	1	Phosphor Bronze	Silver Plated

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.3 .X ±0.3 .XX ±0.3
19143		MEI		
		CHECKED BY	HZF	
		DRAWING BY	LSM	
SCALE	NONE	REV.	A0	UNIT mm

△ A0	NEW RELEASE	HZF	08/14/2024
NO.REV.	REVISIONS	CHK	DATE