



△△ SPECIFICATION

Current Rating:1.0 Amp
 Voltage Rating:30V RMS Max.
 Dielectric Withstanding Voltage:500V AC Min. For 1 Minute
 Insulator Resistance:1000 Megaohms Min. At 500V DC
 Contact Resistance:20 Milliohms Max.
 Operating Temperature:-45°C~+105°C
 Insulator:PBT+30%G.F.(UL94V-0),Black
 △△ Contact:Phosphor Bronze,Gold Flash Over Nickel
 RoHS Compliant

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. △		APPROVED BY MEI		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △ .X ±0.38 △ .XX ±0.25 △ .XXX ±0.15 △ ANG. ±2°
19468		CHECKED BY HZF		
SCALE NONE		DRAWING BY CYP		
REV.	A4	UNIT mm	⊕	

△ A4	Modify Data	HZF	12/09/2019
△ A3	Modify Data	HZF	12/16/2014
△ A2	Modify Data	HZF	03/23/2010
△ A1	Modify Spec.	EMILY	03/24/2009
△ A0	NEW RELEASE	BECKY	2004/07/07
NO. REV.	REVISIONS	CHK	DATE