



**△△ SPECIFICATION**  
 Current Rating:1 Amp  
 Withstanding Voltage:500V AC For 1 Minute  
 Insulation Resistance:1000 Megaohms Min.  
 Contact Resistance:20 Milliohms Max.  
 Operation Temperature:-40°C~+105°C  
 Insulator:PBT+G.F.(UL94V-0)  
 △ Contact:Brass,Selective Gold Flash  
 Over Nickel  
 RoHS Compliant

Pin	A	B	C
6	11.20	5.00	4.00
8	13.20	7.00	6.00
10	15.20	9.00	8.00
12	17.20	11.00	10.00
14	19.20	13.00	12.00
16	21.20	15.00	14.00
18	23.20	17.00	16.00
20	25.20	19.00	18.00
24	29.20	23.00	22.00
26	31.20	25.00	24.00
30	35.20	29.00	28.00
34	39.20	33.00	32.00
40	45.20	39.00	38.00
44	49.20	43.00	42.00
50	55.20	49.00	48.00
60	65.20	59.00	58.00

**4U CON** 元化興業股份有限公司  
 4U CON TECHNOLOGY INC.

DRAWING No. 19558  
 APPROVED BY MEI  
 CHECKED BY HZF  
 DRAWING BY CYP  
 SCALE NONE REV. A4

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE  
 X. ±0.3  
 .X ±0.2  
 .XX ±0.1  
 .XXX ±0.05  
 UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△	A4	Modify Data	HZF	08/31/2016
△	A3	Modify Data	HZF	03/11/2013
△	A2	Modify Data	HZF	10/27/2012
△	A1	Modify Data	HZF	10/31/2011
△	A0	NEW RELEASE	HZF	10/20/2009