



SPECIFICATION

Current:4A Max.
 Voltage:250V AC Max.
 Insulation Resistance:1000 Megohms Min.
 Contact Resistance:10 Milliohms Max.
 Dielectric Withstanding Voltage:1000V AC
 Operation Temperature:0°C~+50°C
 Contact:Brass,Tin Plated Over Nickel
 Housing:PA66(UL94V-2),White
 RoHS Compliant

Pin	A	B
2	3.96	8.06
3	7.92	12.02
4	11.88	15.98
5	15.84	19.94
6	19.80	23.90
7	23.76	27.86
8	27.72	31.82
9	31.68	35.78
10	35.64	39.74
11	39.60	43.70
12	43.56	47.66
13	47.52	51.62
14	51.48	55.58
15	55.44	59.54
16	59.40	63.50

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.35 .XX ±0.10 ANG.
20014		EMILY		
		CHECKED BY		
		HZF		
		DRAWING BY		
		CYP		
SCALE	NONE	REV.	BO	UNIT
				mm

NO.	REV.	BO	NEW RELEASE	HZF	04/21/2015
			REVISIONS	CHK	DATE