




Recommended P.C.B. Layout



**△ SPECIFICATION**

- Current Rating:16 Amp/Way Max.
- Voltage Rating:300V AC
- Contact Resistance:20 Milliohms Max.
- Operation Temperature:-40°C~+105°C
- Soldering Reliability:Test Temperature:  
250°C±10°C/5s Max.
- Withsanding Voltage:2500V AC(1 Minute)  
Test Time=60s/1 PCS
- △ Wire Range:16~30 AWG
- △ Torque:4.5 Kgf.cm/M3.0
- △ Insulating Body(Housing):Polyamide(UL94V-0),Green
- △△ Contact(Metal Housing):Copper Alloy,Nickel Plated
- Solder Pin:Copper Alloy,Tin Plated
- Terminal Screw:Steel,Galvanized With Cr3+ Plated
- RoHS Compliant

**4UCON** 元化興業股份有限公司  
4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.50 .X ±0.30 .XX ±0.20 ANG. ±1°
20064		EMILY		
		HZF		
SCALE		REV.		UNIT
NONE		A4		mm

△ A4	Modify Data	HZF	12/04/2014
△ A3	Modify Data	HZF	06/14/2013
△ A2	Modify Data	HZF	12/15/2011
△ A1	Modify Data	HZF	09/13/2011
△ A0	NEW RELEASE	HZF	11/13/2009
NO. REV.	REVISIONS	CHK	DATE