


File No.	613IC27001	SHEET	1/1




1 Recommended P.C.B. Layout



1



1



1

1 SPECIFICATION

Current Rating:1.5A Max.
Voltage Rating:500V AC/DC
Insulation Resistance:1000 Megohms Min. At 500V DC For 1 Minute
Dielectric Withstanding Voltage:500V AC/Minute
Contact Resistance:30 Milliohms Max.At 20mV Max. 50mA
Operting Temperature:-55°C~+105°C
Insulator:PBT+30%G.F.(UL94V-0),Black
Contact:Brass,Gold Plated On Contact Area,Tin Plated On Solder Tails,Over Nickel
Shell:SPCC,Nickel Plated Over All
Rivet:SPCC,Tin Plated On Solder Tails,Over Nickel
Screw:Brass,Nickel Plated Over All
RoHS Compliant

Pin	A±0.20	B±0.25	C±0.38	D
9	16.92	24.99	30.80	11.08
15	25.25	33.32	39.10	19.39
25	38.96	47.04	53.00	33.24
37	55.42	63.50	69.32	49.86

4UCON 元化興業股份有限公司 4UCON TECHNOLOGY INC.

DRAWING No.	APPROVED BY	CHECKED BY	DRAWING BY	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
21284	MEI	HZF	CYP	.X ±0.25 .XX ±0.15 .XXX ±0.05 ANG ±2°
SCALE NONE	REV. A1			UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
1	A1	Modify Data	HZF	03/27/2018
0	A0	NEW RELEASE	HZF	10/16/2006