


SPECIFICATION

Current:2.1A Max.
Voltage:30V Max.
Withstanding Voltage:500V AC For One Minute
Contact Resistance:30 Milliohms Max.
Insulation Resistance:1000 Megaohms Min.
Temperature Range:-55°C~+85°C
Mating Force:35N Max.
Withdrawal Force:10N Min.
Durability:1500 Cycles Min.
Contact:Brass
Gold Flash On Contact Area,Tin
Plated On Solder Tails,Over Nickel
Insulator:LCP+30%G.F.(UL94V-0),Nature
Shell:Brass,Nickel Plated Over All
RoHS Compliant



Recommended P.C.B. Layout

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

21911

APPROVED BY

MEI

CHECKED BY

HZF

DRAWING BY

HAO

SCALE

NONE

REV.

A1

UNLESS OTHERWISE
SPECIFIED
TOLERANCES ARE


.X ±0.38 X.* ±3°

.XX ±0.25 .X.* ±2°

.XXX ±0.13 .XX.* ±1°

UNIT

mm



NO.	REV.	REVISIONS	CHK	DATE
1	A1	Modify Data	HZF	08/19/2021
2	A0	NEW RELEASE	HZF	07/07/2015