



SPECIFICATION
 Current Rating:1A
 Withstanding Voltage:500V AC At Sea Level
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min.
 Mating Force:3.5 Kg Max.
 Unmating Force:1 Kg Min.
 Operation Temperature:-55°C~+85°C
 RoHS Compliant

| Contact Finish | Insulator Color | Item No. |
|---|-----------------|----------|
| Gold Flash On Contact Area,Tin Plated On Solder Tails,Over Nickel | Black | 22019 |
| Gold Plated 30u" On Contact Area,Tin Plated On Solder Tails,Over Nickel | Black | 11083 |
| Gold Flash On Contact Area,Tin Plated On Solder Tails,Over Nickel | White | 22026 |
| Gold Plated 30u" On Contact Area,Tin Plated On Solder Tails,Over Nickel | White | 22027 |

| No. | Description | Material | Remark | Q'ty |
|-----|-------------|----------|---------------|------|
| ③ | Housing | PBT | | 1 |
| ② | Terminal | C5191H | | 4 |
| ① | Shell | Brass | Nickel Plated | 1 |

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

| | | | | |
|-------------|------|-------------|----|---|
| DRAWING No. | | APPROVED BY | | UNLESS OTHERWISE SPECIFIED TOLERANCES ARE △ X° ±2.0° .X ±0.2 .X° ±1.0° .XX ±0.1 .XX° ±0.5° |
| 22026 | | MEI | | |
| | | HZF | | |
| | | DRAWING BY | | |
| | | CYP | | |
| SCALE | NONE | REV. | A1 | UNIT mm |

| NO. | REV. | REVISIONS | CHK | DATE |
|------|------|-------------|-----|------------|
| △ A1 | | Modify Data | HZF | 12/15/2017 |
| △ A0 | | NEW RELEASE | HZF | 03/29/2015 |