



SPECIFICATION
 2.54mm Insulating Paper Cable #24AWG
 Current Rating:3.0A
 Voltage Rating:300V AC
 Withstand Voltage:1500V AC/Minute
 Conductor:Copper Wire,Tin Plated
 Recommended P.C.B. Hole:Ø0.95mm
 RoHS Compliant

Item No.	Material	Pin	IL	Tp	W	Operation Temperature
22652	NOMEX	6P	76.2	12.7	15.24	-40°C~+105°C
22653	NOMEX	5P	76.2	10.16	12.7	
22654	NOMEX	3P	25.4	5.08	7.62	
22655	NOMEX	5P	50.8	10.16	12.7	
22656	NOMEX	3P	63.5	5.08	7.62	
22657	NOMEX	6P	63.5	12.7	15.24	
22671	NOMEX	4P	25.4	7.62	10.16	
22672	NOMEX	6P	25.4	12.7	15.24	
22673	NOMEX	7P	63.5	15.24	17.78	
22711	NOMEX	14P	152.4	33.02	35.56	
22741	NOMEX	20P	76.2	48.26	50.8	
22674	PET	9P	63.5	20.32	22.86	

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No. 22741
 APPROVED BY MEI
 CHECKED BY HZF
 DRAWING BY LSM
 SCALE NONE REV. A3

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 .X ±0.38
 .XX ±0.25
 UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
3	A3	Modify Data	HZF	08/27/2024
2	A2	Modify Data	HZF	06/28/2024
1	A1	Add P/N Code	HZF	05/16/2024
0	A0	NEW RELEASE	HZF	04/18/2024