



SPECIFICATION

1. Material & Finish
 Insulator: LCP (UL94V-0), Black
 Contact: Brass, Tin Plated
 Solder Tabs: Brass, Tin Plated Over Nickel

2. Electrical Characteristics
 Current Rating: 5A AC, DC
 Voltage Rating: 250V AC, DC
 Contact Resistance: 20 Milliohms Max.
 Insulation Resistance: 1000 Megaohms Min.
 Δ Withstand Voltage: 1500V AC/Minute

3. Environmental Characteristics
 Temperature Range: -40°C ~ +105°C

4. RoHS Compliant

Pin	A	B	C
2	--	6.65	4.30
4	3.00	9.65	7.30
6	6.00	12.65	10.30
8	9.00	15.65	13.30
10	12.00	18.65	16.30
12	15.00	21.65	19.30
14	18.00	24.65	22.30
16	21.00	27.65	25.30
18	24.00	30.65	28.30
20	27.00	33.65	31.30
22	30.00	36.65	34.30
24	33.00	39.65	37.30

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No. 23106

APPROVED BY Jason Wu
 CHECKED BY Leo Han
 DRAWING BY Michelle Lee

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE
 X. ±0.30
 .X ±0.25
 .XX ±0.20
 .XXX ±0.05
 ANG. ±1°

SCALE NONE REV. B1 UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
	B1	Modify Data	HZF	07/21/2025
	B0	Modify Data	HZF	02/20/2023
	B0	NEW RELEASE	HZF	02/20/2023