



△△ SPECIFICATION
 Current Rating:1 Amp
 Withstanding Voltage:500V AC For 1 Minute
 Insulation Resistance:1000 Megaohms Min.
 Contact Resistance:20 Milliohms Max.
 Operation Temperature:-40°C~+105°C
 Insulator:PBT+G.F.(UL94V-0)
 △ Contact:Brass,Selective Gold Flash
 Over Nickel
 RoHS Compliant

Pin	A	B	C
6	11.20	5.00	4.00
8	13.20	7.00	6.00
10	15.20	9.00	8.00
12	17.20	11.00	10.00
14	19.20	13.00	12.00
16	21.20	15.00	14.00
18	23.20	17.00	16.00
20	25.20	19.00	18.00
24	29.20	23.00	22.00
26	31.20	25.00	24.00
30	35.20	29.00	28.00
34	39.20	33.00	32.00
40	45.20	39.00	38.00
44	49.20	43.00	42.00
50	55.20	49.00	48.00
60	65.20	59.00	58.00

4UCON 元化興業股份有限公司
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X. ±0.3 .X ±0.2 .XX ±0.1 .XXX ±0.05	△ A4	Modify Data	HZF	08/31/2016	
07892		MEI			△ A3	Modify Data	HZF	03/11/2013	
		CHECKED BY			△ A2	Modify Data	HZF	10/27/2012	
SCALE		DRAWING BY		△ A1	Modify Data	HZF	10/31/2011		
		NONE		CYP		△ A0	NEW RELEASE	HZF	10/20/2009
REV.		A4		UNIT	NO.REV.		REVISIONS	CHK	DATE
				mm					

