

SPECIFICATION

- Current Rating:10 Amps/Way Max.
- Voltage Rating:300V AC
- Withstanding Voltage:2500V AC For 1 Minute
- Test Time=60s/1 PCS
- Contact Resistance:20 Milliohms Max.
- Wire Range:14~22 AWG
- Operation Temperature:-40°C~+105°C
- Soldering Reliability:Test Temperature=250°C±10°C/5 Seconds Max.
- ⚠ Contact:Copper Alloy,Tin Plated
- ⚠ Wire Guard:Stainless Steel
- ⚠ Insulator Body(Housing):Polyamide+G.F.(UL94V-0), Green

RoHS Compliant

4UCON 元化興業股份有限公司
4UCON TECHNOLOGY INC.

DRAWING No.

18150

APPROVED BY

EMILY

CHECKED BY

HZF

DRAWING BY

SONG

UNLESS OTHERWISE SPECIFIED

TOLERANCES ARE
X. ±0.50
.X ±0.30
.XX ±0.20
ANG. ±1°


SCALE

NONE

REV.

A1

UNIT
mm



NO. REV.

REVISIONS

CHK

DATE

⚠ A1	Modify Data	HZF	05/15/2013
⚠ A0	NEW RELEASE	HZF	02/01/2011