


**△ SPECIFICATION**  
 Current Range:  
 Non-Switching:100mA 50V DC  
 Switching:25mA 24V DC  
 Withstanding Voltage:500V AC 50Hz Or  
 60Hz For 1 Minute  
 Contact Resistance:50 Milliohms Max.(Initial)  
 Insulation Resistance:100 Megaohms Min.  
 At 500V DC,60s±5s  
 △ Operation Temperature Range:-40°C~+85°C  
 Storage Temperature Range:-40°C~+85°C  
 Operation Force:9.8N Max.  
 RoHS Compliant

Pin	A	B
02	6.44	2.54
03	8.98	5.08
04	11.52	7.62
05	14.06	10.16
06	16.60	12.70
07	19.14	15.24
08	21.68	17.78
09	24.22	20.32
10	26.76	22.86
12	31.84	27.94



Item	Description	Q'ty	Material	Remark
①	Terminal	1	Brass	Gold Plated Over Nickel
②	Cover	1	PBT,UL94V-0	Blue
③	Stem	2~12	PBT,UL94V-0	White
④	Contact	2~12	C7035	Gold Plated Over Nickel
⑤	Base	1	PA66+20%G.F.	Black

**4UCON** 元化興業股份有限公司  
 4UCON TECHNOLOGY INC.

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	△ B3 Modify Data △ B2 Modify Data △ B1 Modify Data △ B0 Modify P/N:SWXXSR-RD → SWXXSR-XX-H △ B0 NEW RELEASE NO. REV. REVISIONS	HZF 07/13/2018 HZF 08/11/2015 HZF 04/04/2014 HZF 03/14/2009 HZF 03/14/2009 CHK DATE	
20505		MEI					10mm Over ±0.20
SCALE NONE		CYP					10mm Below ±0.10
REV.	B3	UNIT	mm				