









































					Cable Type				
			Maximum Insulation O.D.		PIC-unfilled and PIC-filled		Pulp or Paper		
Connector	Type Connector	Special Features	Metric (mm)	Inches	AWG	Metric (mm)	AWG	Metric (mm)	
<b>Butt Splicing</b>	<a href="#"><u>UR2</u></a> 	 	Gel-Filled RUS, UL Listed Polypropylene	2.08	0.082	19-26	0.9-0.4	N/A	N/A
	<a href="#"><u>UR2-D</u></a> 	 	Dry Polypropylene	2.08	0.082	19-26	0.9-0.4	19-26	0.9-0.4
	<a href="#"><u>UR</u></a> 	 	Gel-Filled RUS, UL Listed Polycarbonate	1.52	0.060	19-26	0.9-0.4	N/A	N/A
	<a href="#"><u>UY2</u></a> 		Gel-Filled RUS, UL Listed Polypropylene	2.08	0.082	19-26	0.9-0.4	N/A	N/A
	<a href="#"><u>UY2-D</u></a> 		Dry Polypropylene	2.08	0.082	19-26	0.9-0.4	19-26	0.9-0.4
	<a href="#"><u>UY</u></a> 		Gel-Filled UL Listed Polycarbonate	1.52	0.060	22-26	0.7-0.4	N/A	N/A

Butt Splicing	* 557TG 		Gel-Filled Flame Retardant Polypropylene	3.0	0.12	16-22	1.3-0.6	N/A	N/A
	UYF 		Gel-Filled UL Listed Polycarbonate	1.52	0.060	20-26	0.8-0.4	N/A	N/A
	UP2 		Dry Flame Retardant RUS, UL Listed Polycarbonate	1.52	0.060	22-26	0.7-0.4	22-26	0.7-0.4
	UP3 		Dry Flame Retardant RUS, UL Listed Polycarbonate	1.52	0.060	19-26	0.9-0.4	19-26	0.9-0.4
	UAL 		Gel-Filled For Aluminum Polycarbonate	2.08	0.082	17-20AL 19-24 CU	1.2-0.8AL 0.9-0.5 CU	N/A	N/A
	211 		Gel-Filled RUS, UL Listed Polypropylene	2.08	0.082	19-26	0.9-0.4	N/A	N/A
In Line Splicing	* UDW2 		Full Pair Drop Pair Polycarbonate	4.4	0.175	16-19	1.3-0.9	N/A	N/A
	* U1B 		Gel-Filled Full Pair Polycarbonate	3.18	0.125	16-19	1.3-0.9	N/A	N/A

Tap Splicing	<a href="#">UB2A</a> 		Gel-Filled RUS, UL Listed Polypropylene	2.08	0.082	19-26	0.9-0.4	N/A	N/A
	<a href="#">UB2A-D</a> 		Gel-Filled RUS Listed Polypropylene	2.08	0.082	19-26	0.9-0.4	N/A	N/A
	<a href="#">UG</a> 		Gel-Filled RUS Listed Polypropylene	Butt 1.54 Tap 1.12	0.051 0.044	19-26 22-26	0.9-0.4 0.7-0.4	N/A	N/A
	<a href="#">UPB</a> 		Dry UL Listed Flame Retardant Polycarbonate	1.27	0.050	22-26	0.7-0.4	22-26	0.7-0.4
Clear/Cap Only			Gel-Filled RUS, UL Listed Polycarbonate	1.52	0.060	22-26	0.7-0.4	N/A	N/A
	<a href="#">UPC</a> 		UL Listed Flame Retardant Polycarbonate	1.52	0.060	22-26	0.7-0.4	22-26	0.7-0.4